

Ebara AGA15060M (10602 R)



Location **Gauteng, Moot**
<https://www.freedasz.co.za/x-9585-z>

APPLICATIONS

- Domestic pressure boosting
- Small-scale garden irrigation
- Washing vehicles
- Moving clean water in general

TECHNICAL DETAILS

AGA 0.60 - 0.75 also available in "GARDEN" versions i.e. GARDEN (with handle, standard socket and 1.5 m cable) and "GL" (with handle, standard socket and 1.5 m cable and switch)

Available with brass impeller (AGA 0.60 M GO, AGA 0.75 M GO, AGA 1.00 M GO)

TECHNICAL DATA

- Maximum working pressure:
 - 6 bar for AGA 0.60-0.75-1.00
 - 10 bar for the rest of the range
- Maximum temperature of the liquid: 45°C
- Maximum suction depth: 8 m
- Self-ventilated 2 pole asynchronous motor
- Class of insulation F
- IP44 Protection rating

230V ±10%, 50Hz single phase voltage

30/400V 50Hz three phase voltage

• Cast iron pump body

• Seal housing disc in AISI 304 for AGA 0.60-0.75-1.00, in brass for the rest of the range

MATERIALS

- Cast iron pump body
- Seal housing disc in AISI 304 for AGA 0.60-0.75-1.00, in brass for the rest of the range

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | |
| https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z | https://www.freedasz.co.za/x-9585-z |
| Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M | Ebara AGA15060M |

Ãâ Shaft in AISI 416 for AGA 0.60-0.75-1.00, in AISI 303 for the rest of the range

Ãâ Impeller in PPO reinforced with fibreglass for AGA 0.60-0.75-1.00, in brass for the rest of the range

Ãâ Mechanical seal in Carbon/Ceramic/NBR

Ãâ Ejector and nozzle in PPO reinforced with